

EZ-4719-NF DUCT SEALANT

The EZ-4719-NF is a flammable solvent based product used for sealing air conditioning and heating ducts. It has the same general composition as our EZ-6010 but with a higher viscosity level. It is U.L. Listed, premium grade duct sealant.



APPLICATIONS

- Sealing flanges and seam on metal air conditioning or heating duct systems.
- Sealing off sheet metal screw and rivets heads.
- Making air and water tight metal tanks, fume hoods and ventilation systems.
- High strength metal to metal bonds.

ADVANTAGES

- For special jobs requiring a No-Flash, Self-Extinguishing sealant.
- Forms a positive air and water tight seal.
- Bonds to galvanized metal, steel or aluminum.
- Dries rubbery to flex with metal expansion and contraction.
- High level bond adds structural strength to the flange or joint.
- Fast drying and easily applies by brush.
- Specified by Eastman Kodak.

PROPERTIES


Composition:	A nitrate rubber based adhesive that is water and oil resistant. It adheres extremely well to almost all metals and rubber. Once dried, it forms a tough flexible adhesive or sealant. EZ-4791-NF will not flow out after drying when mechanical pressure or flexing occurs.
Color:	Aluminum
Viscosity:	120,000 cp. to 150,000 cp.
Solids:	~41%
Solvents:	Ketones
Storability:	6 months in tightly closed containers
Service Temperature:	-20°F to 200°F
Application and Storage:	60°F to 80°F keep from freezing.
Weight per Gallon:	
Application Techniques:	Caulk gun, putty knife, trowel or heavy brush
Tack Time:	Immediate
Open Time:	15 – 20 minutes
Flammability:	Wet – Non Flash Point. Dry – Self Extinguishing
Coverage Per Gallon:	1/4" bead - 150 linear feet 1" flange - 1800 to 2000 linear feet

Not recommended for exposed outdoor use

Color



Application Methods



503Y
R-9115