

EZ-4719 DUCT SEALANT

This is a flammable solvent based product used for sealing air conditioning and heat ducts. EZ-4719 is a U.L listed, premium grade, reddish brown in color and is for brush applications only.



APPLICATIONS

- Sealing flanges and seams on mental air conditioning or heating duct systems.
- Sealing off sheet metal rivets or screw heads.
- Making air and water tight metal tanks, fume hoods and ventilating systems.
- High strength metal to metal bonds.

ADVANTAGES

- Forms a positive air and water tight seal.
- Bonds to galvanized metal, aluminum or steel.
- Dries rubbery to flex with metal expansion and contraction.
- High level bonds add structural strength to the flange or joint.
- Fast drying and easily applied by brush.

PROPERTIES


Composition:	A nitrate rubber based adhesive that is water and oil resistant. It adheres extremely well to almost all metals and rubbers. Once dried it forms a though flexible adhesive or sealant. Precision EZ-4719 will not flow out after dried when mechanical pressure or flexing occurs.
Color:	Reddish brown
Viscosity:	18,000 cp. to 22,000 cp. with a heavy brush application
Solids:	~48%
Solvents:	Thinning – Methyl Ethyl Ketone Clean-up - Methyl Ethyl Ketone or Lacquer Thinner
Storability:	6 months in tightly closed containers
Service Temperature:	-20°F to 200°F
Application and Storage:	60°F to 80°F keep from freezing.
Weight per Gallon:	9 pounds per gallon
Application Techniques:	
Tack Time:	Immediately.
Open Time:	15 to 20 minutes
Flammability:	Non-Flammable wet. Slow-burning dry.
Coverage Per Gallon:	1/4" bead – 375 linear feet 1" flange - 1800 to 2000 linear feet

Not recommended for exposed outdoor use

Color



Application Methods



PRECISION ADHESIVES

131 Brown Street, Yatesville, PA 18640 | 570.654.6735 | www.precisionadh.com