

PA-114 WATER BASED INSULATION ADHESIVE- NO FLASH WET

The PA-114 is a non-flammable water-based adhesive used for bonding fiberglass insulation to sheet metal. This high performance product provides excellent coverage and adhesion.



APPLICATIONS

- Bonding fiberglass insulation to sheet metal ducts.
- Bonding insulation to other rigid materials.
- Bonding aluminum foils, paper, or vinyl films to fiberglass insulation.
- Formulated for use with Roto-Bonding machines.

ADVANTAGES

- For jobs requiring a no-flash adhesive
- Easy Cleanup with warm water
- Fast drying with high tack
- Excellent coverage

PROPERTIES

Composition:	A high solids, water based adhesive that is non-flammable when wet.						
Color:	Can be White or Gray as applied						
Viscosity:	~10,000 cp						
Solids:	~44%						
Solvents:	Thinning – Water Cleanup – Wet, use warm water. For dry, use chlorinated or aromatic solvents.						
Storability:	6 months in tightly closed containers, ship and store above freezing.						
Service Temperature:	0 to 180°F						
Application and Storage:	50 to 100°F						
Weight per Gallon:	~8 pounds per gallon						
Application Techniques:	Roller coating machine preferred, can also be applied by brush, roller, or spraying.						
Flammability:	Test results performed by United States Testing Company Inc. The test results, calculated in accordance with ASTM E-84-86 for Flame Spread and Smoke developed values area as follows. <table border="0" style="margin-left: 40px;"> <tr> <td>Test Specimen:</td> <td>PA-114</td> </tr> <tr> <td>Flame Spread Index:</td> <td>0</td> </tr> <tr> <td>Smoke Developed Value:</td> <td>5</td> </tr> </table>	Test Specimen:	PA-114	Flame Spread Index:	0	Smoke Developed Value:	5
Test Specimen:	PA-114						
Flame Spread Index:	0						
Smoke Developed Value:	5						

Not recommended for exposed outdoor use

Color



Application Methods

