

PA-116 WATER BASED INSULATION ADHESIVE- SPRAY

The PA-116 is a non-flammable water based adhesive used for primarily used for HVAC applications. This is a fast tack, easy spray adhesive to bond fiberglass insulation to sheet metal.



APPLICATIONS

- Bonding fiberglass insulation to sheet metal ducts
- Bonding insulation to other rigid materials

ADVANTAGES

- Fast tack
- Easy spray
- Excellent coverage
- Excellent bond
- Easy clean up with warm water
- Low odor

PROPERTIES

Composition:	A high solids, water based adhesive that is non-flammable when wet
Color:	White – dries clear
Viscosity:	~1,000 cp
Solids:	~40%
Clean up	Wet, use warm water. For dry, use chlorinated or aromatic solvents.
Storability:	6 months in tightly closed containers, ship and store above freezing.
Service Temperature:	0 °F to 180°F
Application and Storage:	50°F to 100°F
Weight per Gallon:	~8.5 pounds per gallon
Coverage	400-450 square feet per gallon
Application Techniques:	Sprayable, can be applied by brush or roller if desired
Flammability:	Test Results performed by United States Testing Co., Inc. The test results, calculated in accordance with ASTM E-84-91a for Flame Spread and Smoke Developed Values are as follows Test Specimen: PA-116 Flame Spread Index: 0 Smoke Developed Value: 10

Color



Application Methods



Not recommended for exposed outdoor use