

PA-7010 DUCT SEALANT

The PA-7010 is a flammable solvent based product used for sealing air conditioning and heating ducts. It is exceptionally easy to brush and has a smooth creamy appearance. PA-7010 is our economy grade sealant.



APPLICATIONS

- Sealing sheet metal joint and seam in high or low pressure duct systems.
- Sealing off sheet metal screw and rivets heads.
- Making air and water tight all types of galvanized, aluminum or stainless steel sheet metal seams.
- Adhering butted fiberglass duct liner joints to prevent edge pick up by high velocity air.
- Sealing and seaming air systems as used in dryers, air conditioners, etc.

ADVANTAGES

- Forms a tough air-tight and water-tight seal.
- Flexes with expansion and contraction of the sheet metal.
- Can be applied quickly by caulking gun, trowel, putty knife or heavy brush.
- Bonds to galvanized, stainless steel or aluminum.
- Adds structural strength to the flange or seam.

PROPERTIES

Composition:	A rubber compound which cures into a tough, flexible seal. It bonds very well to galvanized stainless steel or aluminum sheet metal. Once cured it will not flow out of the sealed flange under pressure but will flex with expansion and contraction
Color:	Gray
Viscosity:	~100,000 cp.
Solids:	
Solvents:	Toluene and Hexane
Storability:	6 months in tightly closed containers
Service Temperature:	-20°F to 200°F
Application and Storage:	60°F to 80°F
Application Techniques:	Caulk gun, putty knife, trowel or heavy brush
Tack Time:	
Open Time:	
Flammability:	Wet – Flammable. Dry – slow burning
Coverage Per Gallon:	

Not recommended for exposed outdoor use

Color



Application
Methods

